FLIGHT SUMMARY REPORT

Flight Number: 97-071

Calendar/Julian Date: 27 March 1997 • 086

Sensor Package: Thematic Mapper Simulator (TMS)

Area(s) Covered: Central California

Investigator(s): Functional Sensor Flight Aircraft #: 706

SENSOR DATA

Accession #: -----

Sensor ID #: 074

Sensor Type: TMS

Focal Length: -----

Film Type: -----

Filtration: -----

Spectral Band: -----

f Stop: -----

Shutter Speed: -----

of Frames: -----

% Overlap: -----

Quality: -----

Remarks:

Airborne Science and Applications Program

The Airborne Science and Applications Program (ASAP) is supported by three ER-2 high altitude Earth Resources Survey aircraft. These aircraft are operated by the High Altitude Missions Branch at NASA-Ames Research Center, Moffett Field, California. The ER-2s are used as readily deployable high altitude sensor platforms to collect remote sensing and *in situ* data on earth resources, celestial phenomena, atmospheric dynamics, and oceanic processes. Additionally, these aircraft are used for electronic sensor research and development and satellite investigative support.

The ER-2s are flown from various deployment sites in support of scientific research sponsored by NASA and other federal, state, university, and industry investigators. Data are collected from deployment sites in Kansas, Texas, Virginia, Florida, and Alaska. Cooperative international scientific projects have deployed the aircraft to sites in Great Britain, Australia, Chile, and Norway.

Photographic and digital imaging sensors are flown aboard the ER-2s in support of research objectives defined by the sponsoring investigators. High resolution mapping cameras and digital multispectral imaging sensors are utilized in a variety of configurations in the ER-2s' four pressurized experiment compartments. The following provides a description of the digital multispectral sensor(s) and camera(s) used for data collection during this flight.

Thematic Mapper Simulator

The Daedalus Thematic Mapper Simulator (TMS) is a multispectral scanner flown aboard the ER-2 aircraft which simulates spatial and spectral characteristics of the seven Landsat-D Thematic Mapper bands. The specific bands are as follows:

<u>Daedalus</u> <u>Channel</u>	TM Band	Wavelength, mm
1	A	0.42 - 0.45
2	1	0.45 - 0.52
3	2	0.52 - 0.60
4	В	0.60 - 0.62
5	3	0.63 - 0.69
6	С	0.69 - 0.75
7	4	0.76 - 0.90
8	D	0.91 - 1.05
9	5	1.55 - 1.75
10	7	2.08 - 2.35
11	6	8.5 - 14.0 low gain
12	6	8.5 - 14.0 high gain

Sensor/aircraft parameters are as follows:

IFOV: 1.25 mrad

Ground Resolution: 81 feet (25 meters) at 65,000 feet

Total Scan Angle: 430

Swath Width: 8.4 nmi (15.6 km) at 65,000 feet

Pixels/Scan Line: 716

Scan Rate: 12.5 scans/second Ground Speed: 400 kts (206 m/second)

Information on data tape format, logical record format, and scanner calibration data may be obtained from the Aircraft Data Facility, NASA-Ames Research Center, Mail Stop 240-6, Moffett Field, California 94035-1000 (Telephone: 650-604-6252).

DAEDALUS FLIGHT DATA FLIGHT NUMBER 97-071

Check	Actual Check time (GMT)			A c t u a l sca nline		Scan Speed	total G o o d	total Interpolated	total Repeated
Points	begin	e n d	begin	e n d	feet/meter	(rps)	scanlines	scanlines	scanlines
A-B	19:32:34	19:37:06	29896	33296	69500/21189	12.5	3401	0	0
C-D	19:50:42	19:53:06	43496	45296	70000/21341	12.5	1801	0	0
E-F	19:55:46	20:09:08	47296	57322	68000/20731	12.5	10027	0	0

Note: Altitude for E-F begins at 70000ft and ends at 54300ft



